



TECHNICAL DATA SHEET

#3000 HEAVY DUTY CLEAR/STRIPPABLE

For all types of wallcovering. Strippable from unprimed-unsealed drywall

For all types of wallcovering. Strippable from unprimed-unsealed drywall A commercial grade Clear/Strippable adhesive for hanging all types of wallcovering which minimizes the possibility of staining when installing vinyl and delicate coverings such as fabric, string, grasscloth and silk. Also, strippable adhesive for installing fabric backed vinyl over bare, unprimed, unsealed drywall for removal at a later date without severe damage to the drywall. Adhesive must be thoroughly dried, 2-4 weeks depending on humidity and temperature, before strippability without wall damage is possible. High initial wet tack and holding power. Easy to spread, easy to clean up. Mold and mildew resistant. Suitable for use in all pasting machines.

SURFACE PREPARATIONS:

- Apply to clean, dry, structurally sound surface that is free of grease, dirt, cleaning agents and old paste residue.
- Drywall: Will hang all weights of fabric backed vinyl over bare drywall while insuring strippability at a later date without severe damage to drywall surface. All other wallcoverings the drywall should be sealed with suitable primer or sealer.

APPLICATION:

- Use adhesive as is for heavy wallcoverings. Add up to 10% water to dilute for light and medium weight wallcoverings.
- Covers approximately 160 sq. ft./gal.
- Apply a thin coat of adhesive to wallcovering using a roller, brush, or pasting machine.
- Wash excess adhesive from seams and other areas with clean water before it dries.

SPECIFICATIONS:

- Color: Light Cream
- Flammability: Non-Flammable
- Viscosity: 28,000-30,000 cps.
- Normal Storage Life: 1 year
- pH: 6.2 - 7.5
- Packaging: 5 gallon pails
- Weight/Gallon: 9.8 - 10.2
- Coverage: 160 sq. ft./gal.
- Resistance to Mold & Mildew: Excellent
- Clean-up: Water