



TECHNICAL DATA SHEET

#4000 VINYL OVER VINYL CLAY/STRIPPABLE

Strippable adhesive for hanging new Vinyl over existing Vinyl without priming

A commercial grade Clay Based Strippable adhesive for hanging vinyl over vinyl that can be removed at a later date for remodeling without tearing all other vinyls off the wall. High initial wet tack and holding power. Easy to spread. Mold and mildew resistant. Suitable for use in all pasting machines.

SURFACE PREPARATIONS:

- Apply to clean, dry, structurally sound surface that is free of grease, dirt, cleaning agents and old paste residue.
- Be certain existing vinyl wallcovering is firmly attached to the wall. Repair any loose areas or seams.
- Before proceeding with any unusual conditions, consult your adhesive and wallcovering supplier.

APPLICATION:

- Do not dilute. Use adhesive as supplied directly from the container.
- Apply a thin coat of adhesive to the back of the new wallcovering with a brush, roller, or pasting machine.
- Covers approx. 170 sq. ft./gal.

SPECIFICATIONS:

- Be sure to remove excess adhesive with clean water before it dries. Once dry, this adhesive is difficult to remove and may leave a stain if adhesive residue is left on the surface.
- Store and use this adhesive at room temperature for best results.
- Keep container tightly closed when not in use.