



TECHNICAL DATA SHEET

#4100 NAMIL-TRAC® WALLCOVERING ADHESIVE

Developed exclusively for installing NaMil-Trac® Wallcovering

Note: Do not use any other adhesive to install NaMil-Trac® wallcovering or failure will occur. NaMil-Trac® adhesive was developed exclusively for installing NaMil-Trac® Wallcovering, which is a highly fungus and mildew resistant wallcovering. This premium grade clay based strippable adhesive will give excellent adhesion to the NaMil-Trac® backing. Use on drywall, painted surface, or over existing vinyl. Easy to spread. Mold and mildew resistant. Suitable for use in all pasting machines.

SURFACE PREPARATIONS:

- Apply to clean, dry, structurally sound surface that is free of grease, dirt, cleaning agents and old paste residue.
- Glossy Surface: Degloss or prime with suitable primer.
- New Drywall: Can be used to install over bare drywall and be strippable at a later date. If sealing wall is specified, seal with a suitable primer/sealer.
- Existing Vinyl: Be certain existing vinyl is firmly attached to the wall. Repair any loose areas with this adhesive.
- Before proceeding with any unusual conditions, consult with U.S. Vinyl Manufacturing Corporation.

APPLICATION:

- Use adhesive as is for heavy wallcovering. For light to medium weight wallcovering, can be diluted no more than 5%.
- Apply a thin coat of adhesive to wallcovering with a brush, roller, or pasting machine.
- Wash excess adhesive from seams and other areas with clean water before it dries. Washing seams in both vertical and horizontal directions are recommended.
- Use only when temperature is above 50°F.
- Covers approximately 220 sq. ft./gal. when installing NaMil Trac wallcovering over smooth substrates.