



U.S. Vinyl Manufacturing Corporation

Commercial Testing Company Project No. 4502-0529-0514

**SCOPE:** U.S. Vinyl Manufacturing Corporation, as manufactured by the same, 1766 Broomtown Rd., La Fayette, GA 30728 or approved equal, shall meet Federal Specification CCC-W-408D and the standard classification of Wallcovering by Durability characteristics of ASTM-F793-10a for the type and category classified.

**DESCRIPTION:** Vinyl Wallcovering to meet specifications as supplied by manufacturer, vinyl coated and/or vinyl laminated to woven fabric backing.

**PHYSICAL PROPERTIES:**

Total Weight (oz./lin.yd.) 54" width average - 15/16  
Total Weight (oz./sq.yd.) - 9.295

**FLAME SPECIFICATIONS:**

\*Flame Spread - 25  
\*Smoke Developed - 35

**\* FLAMMABILITY TESTS:** All U.S. Vinyl Manufacturing Corporation were tested in 2014 by independent laboratories in accordance with ASTM-E84-13a. All test results surpass Federal standards. Results of these tests are located above. These Universal Flame Spread and Smoke Density values are not intended to reflect hazards presented by this or any material under actual fire conditions.

Vinyl Wallcovering and adhesive shall be mildew resistant. Installer should use a good quality mildew resistant wallcovering adhesive suitable for weight of material. All surfaces should be clean, smooth, dry and structurally sound. Installation instructions supplied by the manufacturer should be followed.

U.S. Vinyl Manufacturing Corporation will supply certificates of compliance upon request that material meets specifications and modifications as outlined herein.